

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
10 July 2008 (10.07.2008)

PCT

(10) International Publication Number  
**WO 2008/083177 A1**

(51) International Patent Classification:  
**G06F 19/00** (2006.01)

[US/US]; 3400 Stevenson Boulevard, #D18, Fremont, CA 94538 (US).

(21) International Application Number:  
PCT/US2007/088858

(74) Agents: **ISRAESEN, R., Burns** et al.; Workman Nydegger, 1000 Eagle Gate Tower, 60 East South Temple, Salt Lake City, UT 84111 (US).

(22) International Filing Date:  
26 December 2007 (26.12.2007)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
11/616,136 26 December 2006 (26.12.2006) US

(71) Applicant (for all designated States except US): **QUESTRA CORPORATION** [US/US]; 3200 Bridge Parkway, Suite 101, Redwood City, CA 94065 (US).


(72) Inventors; and

(75) Inventors/Applicants (for US only): **TAYLOR, John, L.** [US/US]; 42 St. James Drive, Webster, NY 14580 (US). **ROCHTE, Timothy, A.** [US/US]; 448 O'Connor Street, Menlo Park, CA 94025 (US). **BHAGESHPUR, Kiran**

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: MANAGING CONFIGURATIONS OF DISTRIBUTED DEVICES



(57) Abstract: A method manages configurations of devices in a system that communicates information between a device and an enterprise. The method includes building a defined configuration for a device type. The defined configuration includes a set of value requirements. An actual configuration having values associated with the device is compared to the defined configurations. The actual configuration and defined configuration are stored in a database of the enterprise. The method also includes determining, in the enterprise, if the values of actual configuration match the corresponding value requirements of the defined configurations. The method runs business logic associated with the device based on a result from the step of determining if the values of the actual configuration match the corresponding values of the defined configurations. The matched configurations are stored for subsequent use.

WO 2008/083177 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

## 5                    **MANAGING CONFIGURATIONS OF DISTRIBUTED DEVICES**

### BACKGROUND

#### Field of the Art

          The present disclosure generally relates to configuration management databases and, more particularly, to systems and methods for managing configurations of  
10   distributed devices.

#### Background and Relevant Art

          Over time, device manufactures produce many configurations of a given product line as features are added and defects are addressed. Manufactures need to know the configuration of the devices to be able to support the components and provide the proper  
15   “upgrade” path. The configurations of these devices are changed in the field as customers, users, or technicians update hardware and software components. The ability to track the configuration of the devices becomes more complex when the device has been in the field for a long period of time. For example, the life of a CT scanner or X-Ray machine can typically be about 10 to 20 years.

20           Some devices are regulated by the FDA. When updating hardware or software on the regulated devices, the FDA mandates tracking the configuration of certain devices and recording software updates. Records are required, for example, on medical devices that track these updates. Various methods have been used to track updates, ranging from an entire paper system to homegrown systems implemented to track devices in an enterprise  
25   resource planning (ERP) system as part of software bill of materials (BOM). Many manufacturers do not trust the data collected in these systems since the data accuracy relies on the service technician to properly update the device records, which may or may not occur. Sometimes service technicians update devices that were not scheduled to be updated, which further compounds the problems. Another complicating factor is that  
30   some end-customers have the ability to apply updates to the device (e.g., when CDs are shipped by the manufacturer), which leaves the manufacturer to rely on the customer or service technician to report on the status of each update. And on some devices, all control is lost by the manufacturer when the end-customers have the ability to update, add, and/or remove software.

35           Databases have been implemented to store relevant information about the devices in an organization’s information technology (IT) services and to store the relationships between those components. This type of database is typically referred to as a

5 configuration management database (CMDB). A CMDB generally organizes data collected from the components into a way that can be viewed and examined from various perspectives. The components of the information system in this context are referred to as configuration items (CI). The CI can include software, hardware, documentation, personnel, and any other conceivable IT component or combination of components.

10 U.S. Patent Application Publication No. 2005/0193386 to MaCaleb et al. discloses a method for remotely updating software in computer systems. In the method, a client computer sent information about a software application to a server. The server compared the information to the most-updated upgrade package for the software application, which is stored in a part database. When the most up-to-date upgrade package was not installed,  
15 the upgrade was automatically sent to the client system. A client database stored configuration files for the client systems, which included a list of the installed software applications and their versions. MaCaleb discloses a “smart” creation of an update based on the “latest version” of components in the parts database. This system does not maintain information about the configuration of the device, but uses it to determine the  
20 delta from the latest. This system also does not verify that the update will match the configuration of the hardware and software associated with the device.

In U.S. Patent Application Publication No. 2005/0262076 to Voskuil, a computer system is disclosed that is configured for policy-based management of software updates. The system maintained group-policy objects, with which groups of computers are  
25 associated. The system obtained identities of software updates from a source and filter criteria for each update to determine whether the update should be applied to a particular computer. The system assigned newly available updates to selected group-policy objects and added the obtained filter criteria to each group-policy object. The system performed necessary update installations for each group-policy object by determining whether the  
30 computer satisfied the filter criteria for the update for each combination of a computer belonging to a group associated with that policy object and an update assigned to that policy object. If so, the system applied the update to that computer. Although this system checks whether the update should be applied to a particular computer by applying filter criteria, it does not verify the configuration criteria. This system uses group policies  
35 to control software updates.

The subject matter claimed herein is not limited to embodiments that solve any disadvantages or that operate only in environments such as those described above.

- 5 Rather, this background is only provided to illustrate one exemplary technology area where some embodiments described herein may be practiced.

#### BRIEF SUMMARY OF THE INVENTION

10 A method manages configurations of devices in a system that communicates information between a device and an enterprise. The method includes building defined configurations for a device type. The defined configuration includes a set of value requirements. An actual configuration of the device is compared to the defined configuration. The actual configuration and defined configuration are stored in a database of the enterprise. The actual configuration has values associated with the device. The method also includes determining, in the enterprise, if the values of actual  
15 configuration match the corresponding values of the defined configuration. The method runs business logic associated with the device based on a result from the step of determining if the values of the actual configuration match the corresponding values of the defined configurations. The matched configurations are stored for subsequent evaluation.

20 In another aspect of the invention, a system manages configurations of a device associated with a monitor agent. The system includes a server that communicates with the monitor agent. The monitor agent is configured to collect information from the device to obtain an actual configuration of the device. A database is configured to store the actual configuration of the device and a defined configuration of a device type. The  
25 device type is associated with a set of devices. The defined configuration is built for the device type and stored in the database. The defined configuration includes a set of value requirements. The actual configuration has values associated with the device. An enterprise is configured to compare the actual configuration to the defined configuration and to determine whether the values of the actual configuration match the corresponding  
30 values of the defined configuration. The enterprise is configured to store the matching defined configuration and running business logic associated with the device based on a result from the comparison between the values of the actual configuration and the corresponding values of the defined configuration.

35 This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

5 Additional features and advantages will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the teachings herein. Features and advantages of the invention may be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims. Features of the present invention will become more fully  
10 apparent from the following description and appended claims, or may be learned by the practice of the invention as set forth hereinafter.

#### BRIEF DESCRIPTION OF THE DRAWINGS

In order to describe the manner in which the above-recited and other advantages and features can be obtained, a more particular description of the subject matter briefly  
15 described above will be rendered by reference to specific embodiments which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments and are not therefore to be considered to be limiting in scope, embodiments will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

20 Figure 1 illustrates a system managing configurations of distributed devices in accordance with the various embodiments of the present invention;

Figure 2 is a flowchart illustrating a method of managing configurations of distributed devices in accordance an exemplary embodiment of the invention; and

25 Figure 3 is a flowchart illustrating a method of managing configurations of distributed devices in accordance with another exemplary embodiment of the invention.

#### DETAILED DESCRIPTION OF THE INVENTION

The present system and method includes various embodiments for managing configurations of distributed devices. A configuration management database (CMDB) is configured to manage configuration items (CI) of devices. The CMDB tracks and  
30 validates the software and hardware used by the device. The system also tracks the device configuration, including the state of that configuration and can take an appropriate business action. A business action, for instance, can include sending a technician out to a site to update the hardware, such as memory, or complete another action, such as sending a software update or collecting data.

35 In one exemplary embodiment of the system, the CMDB updates the devices with controlled installations over its lifetime to help assure that the device will operate safely after an update installation. Before an update is sent to the device, the CMDB verifies that it is compatible with a defined configuration of the device, which is stored in the

5 CMDB. If the device is not compatible, a business action can occur before the update is sent to the device since the configuration is known. The system can also allow remote updates to the software and/or the device configuration. The “latest” configuration of the device may not necessarily be the only valid configuration and may require changes to the configuration to match a given update. The business logic can take place soon after the  
10 comparison or at a later time. The devices, for example, can be regrouped for later action. The comparison matches are stored in the enterprise so that it can take future action with the devices even if the action takes place days or weeks later.

An IT department for a large corporation may have many thousands of devices to manage on a corporate network, such as server computers, desktop computers, laptops,  
15 firewalls, routers, switches, and the like. IT departments, especially for large corporations, may have problems trying to track the configurations of each device. Device configurations need to be managed efficiently to be able to handle numerous devices. While the device management problem is similar to the IT problem, the complexity of managing devices beyond the corporate network or a network not owned  
20 by the service provider and the expected lifetime of the device makes this problem more complex.

The present invention includes many advantages. Device manufactures will be able to automatically track and manage device configurations to safely update the devices in the field. In addition, the system will streamline device support and service to benefit  
25 businesses, for instance, by reducing costs and improving customer satisfaction. The process is streamlined by driving entitlement validation and expediting problem diagnosis. Furthermore, the system reduces the time it takes to launch a product in the marketplace by improving the time and ability to meet regulatory requirements.

In one application of the invention, for example, the system can be used to track  
30 medical devices that are regulated by the FDA. Regulated devices often require the manufacturer to record device configurations in the event that an important or even dangerous defect is found. The FDA regulates tracking and updating methods for medical devices to insure quick handling of defects that could cause potential safety issues. It is important to know the current device configuration before software or  
35 configuration updates are delivered. The present invention provides a way for the user that installs the update to know that the update is compliant with the device and that the device will operate safely after the installation.

5           A common methodology for dealing with the configuration management problem in the IT space is called IT Infrastructure Library (ITIL). The present invention builds on the ITIL Configuration Management to deal with the issues raised by device manufacturers.

          The system uses Configuration Management. The process identifies and defines  
10   CI in a system, records and reports the status of the CI and Requests for Change, and verifies the completeness and correctness of the CI. The CI is a component of an infrastructure—or an item, such as a Request for Change, associated with an infrastructure—which is or will be under the control of Configuration Management. The  
15   CI may vary widely in complexity, size, and type, from an entire system, including hardware, software, and documentation, to a single module or minor hardware component. The CMDB contains relevant details of each CI and details of the relationships between the CI.

          As shown in FIG. 1, the system can include an enterprise system 100 that communicates with at least one device 200 through a local or global computer network  
20   300, such as the Internet, World Wide Web, or other similar network. The enterprise system 100 includes a server 110 that is connected to a database 120, such as a CMDB. The device 200 communicates with the enterprise 100 at predefined intervals. The device, for instance, can include a power meter, MRI machine, printing press, X-Ray machine, or other devices that include, or can be adapted to include, a monitor agent.  
25   These devices may vary in complexity and may have a set of subsystems associated with them.

          The device 200 contains or is connected through a serial port, USB, network, or the like to a monitor agent 220. The monitor agent 220 is configured to monitor the device status and verify that the device is properly functioning and maintained. The  
30   monitor agent 220 communicates device information to the enterprise 100 as requested by enterprise users or when monitored conditions are met, as defined by rules. The rules can include monitoring rules, which are set up by the user in the monitor agent 220 on the device side, or dynamic group rules, which are set up by the enterprise user to monitor an active status of the devices that belong to the defined group. The status includes  
35   operational status, data readings, or configuration of the device.

          Other devices 400 can be connected to the enterprise system 100 through the network 300, such as the global computer network or other local network. The devices 400 are represented as systems 2 through n to mean any defined amount of devices, which



5 can meet, but not exceed, the capacity of the enterprise system 100. As the users' needs grow, the enterprise system 100 can be modified to match the users' needs, for example, by adding more bandwidth, servers, and/or database capacity. Each of the other devices 400 includes similar components as those defined in the device 200.

10 The monitor agent 220 collects information from the sources of device data, such as a database, a registry, the file system, or data collection protocols. The type of data can include various classes of information including: monitoring data, usage data, and configuration data. This data, for example, can include the operational status, operational data, usage information, location information, environmental information, SW/HW version information (i.e. "configuration" information), or any data available on the device 15 that can be communicated to the enterprise 100. To collect the data, the monitor agent 220 uses plug-in modules to collect device information using either standard or device-proprietary methods. The monitor agent 220 sends data to the enterprise using Web services. The software is not limited to a specific protocol such as simple mail transfer protocol (SMTP) or hypertext transfer protocol (HTTP) but may be adapted to any 20 protocol known by one skilled in the art for data interchange at the hardware device level or at application program level.

The monitor agent 220 can send data sets of information to an enterprise server at the time of a triggering event, and just before and after the event, to capture the condition of the device to provide a baseline. The data can also be collected at a specific time, such 25 as every evening or at the close of business. Each time the device is updated or software revisions are installed, the data also can be collected. If the user needs information outside the prescribed times, a user request can be sent at any time. For instance, if a user wants to verify the configuration of the device and does not want to wait for a prescribed time, a request can be sent immediately.

30 The communication between the enterprise 100 and the monitor agent 220 can be rejected due to firewalls, NAT, etc. that are implemented to block unwanted communication. The system can use a "polling server" model to enhance the ability to communication between the device and the enterprise if needed. The "polling server" model is discussed, for example, in U.S. Patent Publication No. 2003/0118353 entitled 35 Method and Apparatus for Managing Intelligent Assets in a Distributed Environment, which is hereby incorporated by reference in its entirety.

When collecting data from a device, the CMDB collects a configuration baseline. The baseline is a configuration of a product or system established at a specific point in

5 time, which captures both the structure and details of that product or system, and enables that product or system to be rebuilt at a later date. The baseline records a snapshot or a position of the data. Although the position may be updated later, the baseline remains unchanged and available as a reference of the original state and as a comparison against the current position of the device. The CMDB collects and stores the actual configuration  
10 of a device.

The CMDB also stores one or more defined configurations for each device type. The defined configuration is a set of elements that describe the value requirements. The element can include an attribute and a value. The value may be a literal value, set of literal values, or an expression. The expression may contain numerical and Boolean  
15 operators and the like. Defined configurations can be nested into a hierarchy to represent inherently complex devices. In this case, an element references the set of legitimate defined configurations. The collection of elements, including expressions and nested defined configurations, are identified as the value requirements of the defined configuration. The defined configurations allow the CMDB evaluate to stored device  
20 information that can be used to identify a device configuration, which may in turn be used for operations such as verifying whether a software update is compatible with the device.

Enterprise users create defined configurations based on the devices that the manufacturer is building and shipping. The defined configuration is comparable to a “specification” for the device. For example, Company X creates a first version of device  
25 Y. During the creation of the product, enterprise users create many constructs describing device Y, including a device type, defined configurations, and the like, which enable many aspects of remote management. Device Y ships and the enterprise receives actual configuration updates for the purchased devices. The enterprise processes those updates (e.g., matches defined configurations to the device). Some time later Company X works  
30 on new versions of device Y and creates new defined configurations in the process. Once the new device ships, the cycle continues.

A further component of the defined configuration is the state. The value of the state of the device can include, for example, valid, recommended, obsolete, “known bad” and other states known by one skilled in the art. The defined configuration has a state or  
35 status that applies to all devices whose actual configuration matches the defined configuration. The configuration state of the device is on the defined configuration and “inherited” by devices whose actual configuration matches it. If an actual configuration does not match any of the defined configurations, then it is generically said to be

---

5 “invalid.” The state of the device impacts actions taken when a device’s actual configuration changes or when the defined configuration status changes. For example, if a device’s actual configuration changes from obsolete to recommended, no action is required. But if a defined configuration status changes from valid to known bad, immediate action may be required, including software updates, site visits, or other  
10 prescribed actions. If a defined configuration status changes from valid to obsolete, a less aggressive course of action could result, such as a low priority work order to “upgrade the device on the next site visit.”

An actual configuration of the device is also stored in the CMDB. The actual configuration is collected from each device and can, for example, include hardware  
15 versions, software versions, environmental conditions, operational status, operational parameters, and other configuration information that can be collected from the device. The actual configurations, like defined configurations, can be simple or complex, for example, including values nested in a hierarchy.

The defined configuration is associated with a device type, such as a laptop, and  
20 the actual configuration is associated a particular device. The actual configuration, which is collected from the device, can then be compared to the defined configuration for the device type. For example, three devices are compared to a defined configuration of a laptop device type below. The defined type in this example is for laptops where the defined configuration is shown below in Table A:

devicetype = LapTops		
Configuration	IBM Laptops-T23	
State	VALID	
Status	LOCKED	
Mandatory		
Manufacturer	IBM	Y
RAM	>1GB	Y
OS	Windows XP-Pro	Y
HardDisk	Y	
Seagate-M1		<div>WD-32</div> <div>Mfg                  Western Digital</div> <div>Model                24</div>
Mfg	Seagate	
Model	29   30   31	
FWVersion	1.2.29	
Software 1		N
Office 2003		
Word	2003	
Excel	2003	
Software 2		Y
QuestraSA		
Version	5.1.236	

Table A

5           The defined configuration includes various components that can be check against the actual configurations of the devices. The defined configuration includes the following values: the configuration is IBM Laptops-T23; the state is valid; and the status is locked. Other configuration values and types are defined. For example, a configuration type is the manufacturer and the value associated with it is IBM. The defined configuration can

10 also include configuration sets, such as software 1 and software 2 shown above. A configuration set can include values that are grouped together based on various subsystems. The other configuration types are defined accordingly as shown in Table A.

Device actual configurations are compared to defined configurations to determine which, if any, defined configurations match the device. The meaning of the term match,

15 as defined within this application, means that a value in the actual configuration of the

5 device complies with an expression for an element in the defined configuration, which comparison includes, for example, operators such as less than (<), less than or equal to (<=), equal to (=), greater than or equal to (>=), and greater than (>), or other Boolean operators. The elements of a defined configuration can be tagged as elective or mandatory values. If the configuration element is mandatory, then the values of the  
 10 actual configuration must match the respective defined value during the comparison process. If the configuration element is not mandatory, then the component is not required to be present in the system. But if the elective element is present, the configurations must match. When the actual configuration does not match any defined configuration, then the enterprise can be programmed to find the closest match for the  
 15 device, and/or to run business logic to notify the technician or user, or to perform some other action.

Continuing with the example illustrated above, device 1 can include the following actual configuration shown below in Table B:

Device 1 – Actual Configuration		
Manufacturer		IBM
RAM		2GB
OS		Windows XP-Pro
Hard Disk	Mfg	Seagate
	Model	30
	FWVersion	1.2.29
Software1	Word	2003
	Excel	2003
Software2	Version	5.1.236

Table B

20 The actual configuration of device 1 matches the defined configuration in Table A. The hardware and software comply with the requirements in the defined configuration.

A second device in the example includes the actual configuration shown in Table C:

Device 2 – Actual Configuration		
Manufacturer		IBM
RAM		2GB
OS		Windows XP-Pro
Hard Disk	Mfg	Seagate
	Model	30
	FWVersion	1.2.29
Software1	Word	2000
	Excel	2000
Software2	Version	5.1.236

Table C

5           The software in the second device does not match all the fields in the defined configuration because the Word and Excel software applications are 2000, not 2003 as defined by the configuration in Table A. Although Word and Excel software are not mandatory, if the device includes the software, it must match the defined configuration. The mismatch may prompt the system to execute business logic to notify users, to fix, or

10       to schedule an event to fix the unmatched values.

In a third device of the example, the actual configuration is shown in Table D below:

Device 3 – Actual Configuration		
Manufacturer		IBM
RAM		512 MB
OS		Windows XP-Pro
Hard Disk	Mfg	Maxtor
	Model	30
	FWVersion	1.2.29
Software2	Version	5.1.236

Table D

There are two values that do not match the defined configuration in the third device—the size of the memory and the manufacturer. Since the values do not match and

5 these values are mandatory, additional action must be taken to correct the mismatch. For example, new hardware can be installed to update the device to match the defined configuration.

The manufacturers can define and store configurations of devices that will ship to the field. Over the lifetime of a device, the device manufacturers can also assign or  
10 change the state of the device to indicate whether the device or its subsystems have values that are valid, recommended, obsolete, known bad, or the like. The defined configurations may be simple or complex. A complex configuration can include nested configurations or Boolean combinations of attributes and values as discussed above.

The actual configurations of each device are compared with the defined  
15 configurations to determine matches. If a device does not conform to the defined configuration or if the actual device configuration changes, business logic can run to provide notification, modify the device type or group, or schedule an action. The business logic can include, for example, user notification, external system notification (e.g. to schedule a site visit in a CRM system), schedule software updates, or run another  
20 user defined action.

A method of managing configurations is illustrated in FIG. 2 in accordance with the various embodiments of the invention. The method starts in step S20 by building a defined configuration for a device type to validate the devices in the field. Step S20 can occur immediately before or much earlier than any subsequent step, for example, days,  
25 weeks, months, or even years later. A technician can build the defined configuration based on the hardware and software specification for the device. Various elements can be added to the defined configuration to match the definition of the device with the specification. If a certain component is required, the element can be tagged as mandatory. The values in the actual configuration of the device must comply with the  
30 mandatory values of the defined configuration.

Once the defined configuration is built for the device type, the system may verify each device in the device type. Generally, devices configurations are matched when the actual configuration is sent from the device to the enterprise to reduce resource utilization, such as server load. A user can also request the system to match all devices  
35 based on a previously stored configuration. The events that cause the actual configuration to be sent from the device to the enterprise include: agent startup, installation of new software through the system, and manual requests from a user of the agent user interface. This event can trigger the configuration comparison and matching. In step S21, the actual

5 configuration of the device is compared to the defined configuration. When the actual configuration does not match the defined configuration in step S22, the system can run business logic for the device in step S23 to notify users about the mismatch or to schedule an action to fix the noncompliant software or hardware in the device. The method then advances to step S25 to check if the validation process is complete for all the devices in  
10 the device type group.

When the actual configuration matches the defined configuration in step S22, the system can run business logic for the device in step S24 such as sending an update to the device, associating a state with the device, or grouping the device with other devices. The method then advances to step S25. When all the devices have been compared and  
15 matched, the process ends for the given device type.

If the validation process is not complete for all devices in the device type, the process continues to step S26 where it advances to the next device. The method then repeats the process in step S21 to compare the actual configuration of the next device in the device type against the defined configuration. The process continues until the  
20 analysis is complete for the device type or group of devices that are associated with the device type.

Another embodiment of the invention is illustrated in FIG. 3. A method of managing configurations starts in step S30 by building a defined configuration for a device type to validate the devices in the field. The defined configuration can be built  
25 based on the device hardware and software specification. The defined configuration includes various elements that are needed to match the definition of the device with the requirements. Some elements can be tagged as mandatory if a component is required. If so, the values in the actual configuration of the device must meet or exceed the mandatory values of the defined configuration.

30 In step S31, the actual configuration of the device is compared against the value requirements in the defined configuration. The system then determines whether the actual configuration matches the defined configuration in step S32. If the values match, then in step S33 the system runs business logic associated with the device, such as sending a software update or configuration updates. If not, the system can run another set  
35 of business logic for the device as shown in step S34 to notify users about the mismatch or to schedule an action to fix the noncompliant software or hardware in the device. After step S33 or step S34 is complete, the process ends for the device and the data from the determined matches are stored in the database.



5           The system can be configured to send the software update to the device after it has been verified. In another embodiment, the system can be configured to send the update to a group of devices that have been verified at one time. After the device is verified, it can be placed in a group that corresponds to the updated devices. The groups can be based on a group type or set of group types. Device grouping is discussed in more detail below.

10           Optionally, the devices can be grouped together to simplify actions across multiple devices. The devices can be grouped based on certain criteria, such as geography, software application, version, extension, device type, model number, installation, division, or other device parameter. For example, the verified devices can be grouped together and the nonconforming devices can be placed in a separate group. A  
15           device can be added or removed from a given group dynamically without requiring input from any user. The movement in and out of groups can occur when an event triggers the group evaluation, such as (a) after device registration or profile updates, (b) when receiving new device operational, status, environmental data, (c) when receiving new configuration information (i.e. new versions), or (d) when alarms and/or alerts are created  
20           for a device. These groups are created automatically and may define where notifications are sent and associate other business logic to devices, such as data collection schedules, software/patch distribution schedules, and the like. The groups are arranged or created such that an administrator is no longer required review each device to verify present device conditions.

25           The system can collect the actual configuration of a device in the same manner as described above with respect to grouping. The data, for example, can be collected periodically, ad hoc, and on events that are likely to change the configuration, such as software and hardware upgrades. When the device information is received, business logic can be executed to send notifications or perform another action.

30           The devices can be associated with defined groups in the system to help organize the devices so users can locate the device easily. In addition, “bulk” operations can be performed on multiple devices including, for example, software updates or data collection, such as data readings, configuration information, file transfers, and the like. The groups can also control escalation of alert notifications. Furthermore, they can be  
35           used to control access to devices, for example, which users can view or change information regarding certain devices.

          A group hierarchy also can be created if desired. The group hierarchy can include dynamically and statically defined groups, where dynamic group hierarchies start at a

5 statically defined root group. A dynamically defined group is a group to which devices are assigned automatically. To set up a dynamic group, the user defines it by setting up criteria against which the devices are evaluated to determine their membership in the group. The statically defined group is a group whose device membership has been manually defined by an administrator. The administrator creates the group and associates  
10 devices with it. When a new device is added to the system, the administrator manually associates it with a static group. The dynamic hierarchical groups are created based on analysis of dynamic group rules and information collected directly from the device.

A dynamic group rule can be created to specify how devices will be automatically organized into groups when those devices are manually created or provide information to  
15 the enterprise. Devices can be automatically associated with groups based on a set of rules or some aspect of their profiles. As devices are added to the system or provide updated information to the enterprise, they are automatically associated with the applicable dynamic groups. A dynamic group rule causes groups to be created. The first time a device is found to match the membership criteria for a dynamic group that group is  
20 created. The static and dynamic groups have a parent group. Those at the top level have a special built-in logical parent are called a root. Groups whose parent is the root are called root groups.

Automatic groupings can be created based on device configuration data. For example, the group can be defined from the software, firmware, hardware revision  
25 information, as well as other actual configuration information. The groups are matched with defined configurations on the enterprise system 100.

The groups can also be automated based on extended and configurable registration information. The information, for example, can include device location, such as country, state, city, building, etc., or other customer information, like company name, group,  
30 responsible party, and other identifying information.

Business rules can also be applied at the device or the enterprise. The device can be grouped according to the business rule. For example, devices can be grouped based on a dynamic device property exceeding a threshold, such as a temperature, duration, pressure, or the like. If the collected information of the device meets a monitoring rule,  
35 then information can be sent to the enterprise where the system evaluates the collected information for dynamic group evaluation. The addition and removal of devices to and/or from groups manages the group-based business logic. The group-based business logic is disassociated from a group when the device is automatically disassociated from the group

5 and group based business logic is associated to a new group when the device is automatically associated with the new group. For example, when a group has been updated, a new group can be created with the updated devices.

Automatic grouping also can be based on a device condition, such as an alert or an alarm. Alarms can be created by the monitor agent or by the enterprise system rules.  
10 When an alarm or alert is created, it triggers dynamic group rule evaluation. Alarms and alerts are defined by rules or business logic, which will be discussed below. The devices that are in a specified alert state, that is, meet a condition defined by a rule, can all be grouped together.

Business logic can also be applied to groups. For instance, if the actual  
15 configuration of a device does not match the defined configuration, then business logic can be applied. The business logic is applied to or removed from devices that enter or leave a dynamic group, respectively.

A dynamic group rule can create a hierarchy of groups, not just one flat group. A device can belong to multiple groups and subgroups in the hierarchy. The user selects  
20 which static groups to associate with the device or creates a rule specifying the device data that should be used to match the current device conditions. During the selection process, for instance, the user may choose to group the device by location, device type, and software application. The device location may be a high level group, which includes many other device types. Thus, the device type group becomes a subgroup of the device  
25 location group. Likewise, different software application groups may be found in the device type group making it a subgroup of the device type group. This relationship creates a hierarchy of groups and subgroups—the subgroups being defined within another group. Some groups may be entirely defined within a group while others may be partially defined within the group. The hierarchical groups are defined accordingly for each  
30 device.

The business logic can send notifications to users about the current or updated status of the device. The notifications can be sent to business systems or users, such as field service technicians, device operators, etc. assigned to groups that are associated with a specific device in an alarm or alert condition. In one embodiment of the present  
35 invention, the notifications are defined as alarms and alerts. The alarm is a notification that is recorded and processed when a condition exists. For example, an alarm can be triggered when the actual configuration of a device does not match the defined configuration. The alarm is tracked and stored in a database. An alert is an action to be

5 taken when the alarm condition exists. The alert, for example, can be a user notification sent by e-mail or an event notification to another business system, such as a CRM system. One alarm can generate multiple alerts, for instance, one alarm can cause an e-mail message to be sent to users and a separate notification to other business systems.

10 In an alternative embodiment, the notifications can escalate. After a notification has been sent to a group, if it has not been acknowledged within a defined time limit, then the notification is escalated to the next higher-level group in the hierarchy. And if the notification is not acknowledged on the higher level, then it is escalated to the next group and so forth. If the notification is acknowledged within the defined time limit, then it will not escalate to the next group. The time limit can be any defined amount of time.  
15 Typically, the time limit is defined in hours. In one example, the time limit may be set between three and five hours from the notification. The selection of a time limit is not limited to any particular range since it is based on user input.

The enterprise system 100 can include the various embodiments discussed above. The information collected from the devices is managed through the enterprise system 100  
20 to reduce the administrative time it takes to monitor and update each device individually. The actual and defined configurations of the devices are stored in the CMDB. The values in the actual configuration are checked against the value requirements in the defined configuration to determine the configuration of the device. Business logic can be run based on the results of the comparison, for example, verifying that the software update  
25 will be compatible with the existing device and subsystems before the update is sent to the device. If the values are not compatible, business logic can be executed and a technician can update the device to make it compliant with the defined configuration. The present invention provides controlled updates to help assure that the devices will function properly after the installation is complete.

30 The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the  
35 claims are to be embraced within their scope.

5

CLAIMS

What is claimed is:

1. In a system that communicates information between a device and an enterprise, a method for managing configurations of the devices, the method comprising:  
building a defined configuration for a device type, the defined configuration  
10 including a set of value requirements;  
comparing an actual configuration of the device to the defined configuration, the actual configuration and defined configuration being stored in a database of the enterprise, the actual configuration having values associated with the device;  
determining, in the enterprise, if the values of actual configuration match the  
15 corresponding value requirements of the defined configuration;  
running business logic associated with the device based on a result from the step of determining if the values of the actual configuration match the corresponding value requirements of the defined configuration; and  
storing the matched configurations for subsequent use.
- 20 2. The method of claim 1, further comprising a step of collecting information from a device information source to obtain the actual configuration of the device.
3. The method of claim 1, further comprising a step of establishing at least one dynamic group rule based on the result from determining if the values of the actual configuration match the corresponding value requirements of the defined configuration.
- 25 4. The method of claim 1, further comprising a step of sending a notification based on the result from the step of determining if the values of the actual configuration match the corresponding value requirements of the defined configuration.
5. The method of claim 4, wherein the notification is an alert and the step of sending the notification further comprises sending the alert to a recipient including at  
30 least one of a user and a business system.
6. The method of claim 5, further comprising a step of determining the recipient of the notification using group associations of a specific device in at least one of an alarm and alert condition.
7. The method of claim 1, wherein the step of building the defined  
35 configuration for the device type further includes setting at least one mandatory element in the defined configuration.
8. The method of claim 7, wherein the mandatory element includes a mandatory value requirement and the step of determining if the values of actual

5 configuration match the corresponding value requirements of the defined configuration further includes requiring a match of the actual configuration to the mandatory value requirement of the defined configuration.

9. The method of claim 7, wherein the step of determining if the values of actual configuration match the corresponding value requirements of the defined  
10 configuration further includes requiring a match if an elective value requirement of the defined configuration is present in the actual configuration.

10. The method of claim 1, further comprising a step of automatically associating the device with a group that reflects the result from the step of determining if the values of the actual configuration match the corresponding value requirements of the  
15 defined configuration.

11. The method of claim 1, wherein the step of determining if the values of actual configuration match is repeated for each device in a set of devices.

12. The method of claim 11, wherein the step of sending an update and the step of running business logic are performed after the step of determining if the values of  
20 actual configuration match for all devices in the set of devices.

13. The method of claim 1, wherein the step of determining if the values of actual configuration match the corresponding values of the defined configuration occurs after receiving the actual configuration from a device.

14. The method of claim 1, wherein the step of running business logic includes  
25 sending at least one of a software and configuration update to the device.

15. The method of claim 1, wherein the step of determining if the values of actual configuration match the corresponding value requirements of the defined configuration further includes using an expression containing at least one of a Boolean operator and numerical comparison operator to make the comparison between the values.

30 16. The method of claim 1, wherein the step of building a defined configuration for a device type further includes building complex defined configurations to identify the value requirements.

17. A system for managing configurations of a device associated with a monitor agent, the system comprising:

5           a server that communicates with the monitor agent, the monitor agent being configured to collect information from the device to obtain an actual configuration of the device;

          a database configured to store the actual configuration of the device and a defined configuration of a device type, the device type being associated with a set of devices; the  
10   defined configuration being built for the device type and stored in the database, the defined configuration including a set of value requirements, and the actual configuration having values associated with the device; and

          an enterprise configured to compare the actual configuration to the defined configuration and to determine whether the values of the actual configuration match the  
15   corresponding value requirements of the defined configuration, the enterprise being configured to store the matching defined configuration and run business logic associated with the device based on a result from the comparison between the values of the actual configuration and the corresponding values of the defined configuration.

18.    The system of claim 17, wherein the enterprise is configured to collect  
20   information from a device information source to obtain the actual configuration of the device.

19.    The system of claim 17, wherein the enterprise is configured to run the business logic if a change is determined when the actual configuration of the device is compared to the defined configuration.

20.    The system of claim 19, wherein the business logic includes sending a  
25   notification to at least one user including at least one of an alarm and an alert.

21.    The system of claim 20, wherein the alert is sent when the value requirements of the defined configuration do not match the actual configuration.

22.    The system of claim 17, wherein the enterprise is configured to  
30   automatically associate the device with a group that reflects the result from the comparison between the values of the actual configuration and the corresponding value requirements of the defined configuration.


23.    The system of claim 17, wherein the enterprise is configured to repeat the comparison between the values in the defined configuration and values of actual  
35   configuration for other devices in the set of devices.

24.    The system of claim 17, further comprising at least one mandatory value requirement in the defined configuration, the actual configuration being matched to the mandatory value requirement.


- 5            25.     The system of claim 17, further comprising an elective value requirement in the defined configuration, a match being required if the elective value requirement is present in the actual configuration.




1/3

**Figure 1**

2/3

**Figure 2**

3/3

**Figure 3**

## INTERNATIONAL SEARCH REPORT

International application No.  
**PCT/US2007/088858****A. CLASSIFICATION OF SUBJECT MATTER****G06F 19/00(2006.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 8 G06F 15/16, 9/46, H04Q 7/20

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Utility models and applications for Utility models since 1975

Japanese Utility models and applications for Utility models since 1975

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKIPASS(KIPO internal) &amp; keywords : device, management, configuration, OMA, DM

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2005-0055397 A1 ( ZHU, Y. et al. ) 10 March 2005 See figures 3-4, paragraphs [0004]-[0006], [0019]-[0020], [0027]-[0028]	1-25
Y	US 2006-0236325 A1 ( RAO, B. R. et al. ) 19 October 2006 See abstract, figures 1, 3, paragraphs [0005]-[0012], claims 1, 22	1-25
A	US 7,028,081 B2 ( KAWASHIMA, M. ) 11 April 2006 See abstract, figure 1	1, 17

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

21 MAY 2008 (21.05.2008)

Date of mailing of the international search report

**21 MAY 2008 (21.05.2008)**

Name and mailing address of the ISA/KR

Korean Intellectual Property Office  
Government Complex-Daejeon, 139 Seonsa-ro, Seo-  
gu, Daejeon 302-701, Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

Park Ji Eun

Telephone No. 82-42-481-8537



**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No.

**PCT/US2007/088858**

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2005-055397 A1	10.03.2005	CN1598851A	23.03.2005
		EP01515571A2	16.03.2005
		EP1515571A2	16.03.2005
		JP17085281	31.03.2005
		JP2005085281A2	31.03.2005
		KR1020050025913	14.03.2005
		KR2005025913A	14.03.2005
US 2006-236325 A1	19.10.2006	None	
US 07028081 B2	11.04.2006	US20030115314A1	19.06.2003
		US2003115314A1	19.06.2003
		US2003115314AA	19.06.2003